

Architectural floor plan of a building section, showing structural details and dimensions. The plan includes a central corridor and two main rooms. Key features include:

- Dimensions:**
 - Room widths: 3150 mm (left), 3150 mm (right), 2580 mm (bottom left), 2680 mm (bottom right).
 - Room depths: 3000 mm (left), 2000 mm (right).
 - Overall width: 5150 mm.
 - Overall depth: 4580 mm.
- Structural Details:**
 - Štukové římsy v plném rozsahu obnovit dle původních** (Plaster cornices to be fully restored according to the original).
 - Průvlak: 3x profil I 240** (Cross-section: 3x profile I 240).
 - Dimenze a technologie provádění viz část stavebně-konstrukční** (Dimensions and technology of execution see the construction-structural part).
- Levels and Elevation:**
 - ±0,000 (Ground level)
 - +3,925 (Roof level)
 - +3,470 (Roof level)
 - +3,150 (Roof level)
 - +0,035 (Roof level)
 - 0,200 (Basement level)
 - 0,440 (Basement level)
 - 2,880 (Basement level)
 - 0,620 (Basement level)
- Other Features:**
 - Windows: 1200 mm wide, 1500 mm high.
 - Doors: 1200 mm wide, 2000 mm high.
 - Stairs: 1200 mm wide, 1500 mm high.
 - Basement: 2000 mm wide, 2000 mm high.

Z důvodu zachování soudržnosti zdiva v místě
uložení průvlaku se PŘEDEPISUJE provést
rozpojení zdiva ŘEZÁNÍM

The drawing is a vertical cross-section of a building facade. At the top, a horizontal line is labeled $+3,925$. Below it, a row of six square windows with 'X' marks is shown. A vertical line from the top center is labeled $P3$. Below the windows, a horizontal line is labeled $+3,350$. A diagonal line from the top center to the bottom left is labeled $+3,150$. A vertical line from the bottom left to the bottom right is labeled $31,50$. A horizontal line in the middle is labeled $\pm 0,000$. Below it, a horizontal line is labeled $-0,620$. A vertical line from the middle to the bottom is labeled $25,80$. At the bottom, a horizontal line is labeled $-2,880$. A diagonal line from the middle to the bottom left is labeled $P1$. A vertical line from the bottom left to the bottom right is labeled 300 . The text *Nově realizovaný otvor* is written along the diagonal line from the top center to the bottom left. The text *Štukové římsy v plném rozsahu obnovit dle původních* is written along the diagonal line from the top center to the bottom right. The drawing shows the building's structure, including the roof, walls, and foundation. The foundation is hatched with diagonal lines. The drawing is a technical architectural drawing with dimensions and labels.

—Z důvodu zachování soudržnosti zdiva v místě uložení průvlaku se PŘEDEPISUJE provést rozpojení zdiva ŘEZÁNÍM

ZAKÁZKA:			
Stavební úpravy učebny chemie a adaptace učebny biologie			
Adresa: Ukrajinská 379, 436 01 Litvínov		Č. KOPIE:	MĚŘITKO: 1:50
OBSAH:			
Chemie - řezy		DATUM:	04/2016
		FORMÁT:	4 x A4
DÍL: STAVEBNÍ	Č.VÝKR.: S-06	STUPEŇ:	DSP
KRESLIL: Ing.arch. Filip Müller	AUTORIZOVAL: Ing. Oldřich Slonek (ČKAIT 0400727)		